

View Online at <https://aerobasegroup.com/nsn/5930-00-115-8510>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Height:**

2.265 inches

**Overall Width:**

0.546 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

0.562 inches

**Body Width:**

0.546 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.017 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked out and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 50.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Test Data Document:**

81349-mils8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0