

View Online at <https://aerobasegroup.com/nsn/5930-00-115-8522>

Thread Class:

2a single mounting facility

Thread Length:

0.218 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.580 inches

First Flat Length:

0.100 inches single actuator

Flat Height:

0.090 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.472 inches single actuator

Overall Diameter:

0.720 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

10 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flat, undercut single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+25.000 to 36.000 inch-ounces single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts and terminal surfaces gold and contacts and terminal surfaces silver

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0