

View Online at <https://aerobasegroup.com/nsn/5930-00-116-2737>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.047 inches

Overall Height:

1.500 inches

Overall Width:

1.000 inches

First Flat Length:

0.870 inches single actuator

Flat Height:

0.195 inches single actuator and 0.199 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

1.000 inches single actuator

Nonturn Device Radius:

0.434 inches at 6: 00 o'clock and 0.454 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Terminal single mounting facility

Features Provided:

Cam actuated

Contact Voltage Rating In Volts:

250.0 ac at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, both positions maintained single switch single section rear

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Quick disconnect, male

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0