

View Online at <https://aerobasegroup.com/nsn/5930-00-116-2737>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.047 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.000 inches

**First Flat Length:**

0.870 inches single actuator

**Flat Height:**

0.195 inches single actuator and 0.199 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Nonturn Device Radius:**

0.434 inches at 6: 00 o'clock and 0.454 inches at 6: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Terminal single mounting facility

**Features Provided:**

Cam actuated

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from nonturn device single actuator

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, both positions maintained single switch single section rear

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

25.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0