

View Online at <https://aerobasegroup.com/nsn/5930-00-116-2769>

Thread Class:

2a single mounting facility

Thread Length:

0.181 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.090 inches

First Flat Length:

0.100 inches single actuator

Flat Height:

0.095 inches single actuator and 0.120 inches single actuator

Shaft Diameter:

0.120 inches single actuator and 0.125 inches single actuator

Shaft Length:

0.847 inches single actuator

Overall Diameter:

0.720 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flat, undercut single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+25.000/+36.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load ac at sea level and 50.0 milliamperes inductive load ac at sea level

Precious Material And Location:

Contact and terminal surfaces gold and terminal surfaces and contacts silver

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0