## NSN 5930-00-116-3272

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-116-3272

Hazardous Locations/environmental Protection:
Driptight and dustproof and oiltight and watertight
Overall Length:
5.406 inches
Overall Height:
2.438 inches
Overall Width:
2.312 inches
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.438 inches
Housing Length:
4.500 inches
Housing Width:
2.312 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
160.0 inch-ounces
Actuator Movement:
6.0 pretravel degrees and 75.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 12.000 amperes inductive dc and 10.000 amperes resistive ac and 12.000 amperes inductive ac

## NSN 5930-00-116-3272

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0