

View Online at <https://aerobasegroup.com/nsn/5930-00-116-3272>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Driptight and dustproof and oiltight and watertight

Overall Length:

5.406 inches

Overall Height:

2.438 inches

Overall Width:

2.312 inches

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.438 inches

Housing Length:

4.500 inches

Housing Width:

2.312 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

160.0 inch-ounces

Actuator Movement:

6.0 pretravel degrees and 75.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 12.000 amperes inductive dc and 10.000 amperes resistive ac and 12.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0