

View Online at <https://aerobasegroup.com/nsn/5930-00-116-4929>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.656 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Height:**

4.000 inches

**Overall Width:**

4.000 inches

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

98853

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

24 each section periphery

**Mounting Facility Circle Radius:**

1.469 inches 2nd mounting facility

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Three position circular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Terminal Type:**

Pin

**Contact Switching Action:**

Breaks before makes each section periphery

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0