## NSN 5930-00-116-4929

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-116-4929

2b 2nd mounting facility Thread Length: 0.656 inches 1st mounting facility

**Thread Class:** 

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Height:** 

4.000 inches

**Overall Width:** 

4.000 inches

**Individual Section Quantity:** 

2

**Knob Manufacturer Code:** 

98853

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section periphery

**Throw Quantity:** 

24 each section periphery

**Mounting Facility Circle Radius:** 

1.469 inches 2nd mounting facility

**Mounting Method:** 

Threaded hole 2nd mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 2nd mounting facility

**Thread Size:** 

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Mounting Facility Pattern:** 

Three position circular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:** 

24 single actuator

**Terminal Type:** 

Pin

**Contact Switching Action:** 

Breaks before makes each section periphery

**Contact Load Current Rating:** 

10.0 amperes resistive load ac at sea level

## NSN 5930-00-116-4929

Rotary Switch - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Square wafer, panel mount

**Thread Series Designator:** 

Unef 1st mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0