

View Online at <https://aerobasegroup.com/nsn/5930-00-116-4929>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.656 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

4.000 inches

Overall Width:

4.000 inches

Individual Section Quantity:

2

Knob Manufacturer Code:

98853

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

24 each section periphery

Mounting Facility Circle Radius:

1.469 inches 2nd mounting facility

Mounting Method:

Threaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Terminal Type:

Pin

Contact Switching Action:

Breaks before makes each section periphery

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0