

View Online at <https://aerobasegroup.com/nsn/5930-00-116-4947>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Width:

Between 2.095 inches and 2.155 inches

Body Length:

Between 3.010 inches and 3.070 inches

Body Height:

1.750 inches

Case Material:

Plastic

Actuator Length:

1.570 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

3.000 inches

Actuator Roller Diameter:

Between 0.720 inches and 0.780 inches

Actuator Roller Width:

Between 0.282 inches and 0.342 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.266 pretravel inches and 0.219 overtravel inches and 0.165 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0