NSN 5930-00-116-6576

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-116-6576

| Overall Height: |
|--|
| 1.578 inches |
| Overall Width: |
| 1.422 inches |
| Body Thickness: |
| 0.620 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.155 inches single mounting facility |
| Distance Between Mounting Facility Centers: |
| 1.250 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Strut single mounting facility and unthreaded hole single mounting facility |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 300.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level |
| Precious Material And Location: |
| Contact and rotor blade surfaces silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Switch section, rotary |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |
| |
| |
| |