## NSN 5930-00-117-3814

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-117-3814

Thread L	_ength:
----------	---------

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Watertight

**Overall Length:** 

2.031 inches

**Overall Height:** 

2.312 inches

**Overall Width:** 

1.968 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.186 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Individual Section Quantity:** 

1

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

**Throw Quantity:** 

3 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

35.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

15.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:** 

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

**Shaft Type:** 

Round, flatted single actuator

## NSN 5930-00-117-3814

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section front
<b>Switch Actuator Positioning Increment:</b>
15.0 degrees single actuator
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0