

View Online at <https://aerobasegroup.com/nsn/5930-00-118-8094>

Thread Length:

0.688 inches single threaded bushing

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 4.036 inches and 4.968 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

Between 2.937 inches and 2.999 inches

Temperature Sensing Element Type:

Expanding shell

Width Across Flats:

1.125 inches

Mounting Method:

Threaded bushing

Features Provided:

Locking device

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage2.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+600.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

55.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage240.0 ac at sea level second voltage115.0 dc at sea level third voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0