

View Online at <https://aerobasegroup.com/nsn/5930-00-119-4616>

Overall Length:

4.000 inches

Overall Height:

6.125 inches

Mounting Slot Width:

0.375 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

2.312 inches

Longest Vertical Distance Between Mounting Centers:

0.812 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and slot and unthreaded hole

Features Provided:

Electrical access port and manual reset button

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Sensing Element Burst Pressure:

50.00 pounds per square inch gage

Terminal Type:

Screw

Contact Load Current Rating:

12.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable, manual reset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+150.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

5.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0