NSN 5930-00-119-4616

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-119-4616

Overall Length:
4.000 inches
Overall Height:
6.125 inches
Mounting Slot Width:
0.375 inches
Body Height:
3.250 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Longest Horizontal Distance Between Mounting Centers:
2.312 inches
Longest Vertical Distance Between Mounting Centers:
0.812 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and slot and unthreaded hole
Features Provided:
Electrical access port and manual reset button
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Sensing Element Burst Pressure:
50.00 pounds per square inch gage
Terminal Type:
Screw
Contact Load Current Rating:
12.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable, manual reset and actuation point adjustable, preset
Contact Adjustment Range:
+0.00/+150.00 actuation point pounds per square inch gage
Contact Adjustment Type:

Contact Stimulus Rating:

External actuation point screw

5.00 actuation point pounds per square inch

NSN 5930-00-119-4616

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 240.0 ac at sea level single voltage Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0