

View Online at <https://aerobasegroup.com/nsn/5930-00-119-9120>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Height:

0.641 inches

Overall Width:

0.641 inches

Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 1.786 inches and 1.828 inches

Body Width:

Between 0.625 inches and 0.657 inches

Body Height:

Between 0.625 inches and 0.657 inches

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.148 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.687 inches

Actuator Free Position Height:

Between 0.802 inches and 0.822 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 0.359 inches and 0.391 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.187 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0