

View Online at <https://aerobasegroup.com/nsn/5930-00-119-9121>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.562 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Height:**

1.812 inches

**Overall Width:**

0.641 inches

**Bushing Length:**

Between 0.359 inches and 0.391 inches

**Body Length:**

Between 1.796 inches and 1.828 inches

**Body Width:**

Between 0.625 inches and 0.657 inches

**Body Height:**

Between 1.109 inches and 1.141 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.142 inches and 0.148 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.245 inches and 0.255 inches

**Actuator Height:**

0.687 inches

**Actuator Free Position Height:**

Between 0.802 inches and 0.822 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

0.391 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

0.050 pretravel inches and 0.187 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0