

View Online at <https://aerobasegroup.com/nsn/5930-00-120-1033>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Weatherproof and watertight

**Overall Length:**

8.594 inches

**Overall Height:**

3.656 inches

**Overall Width:**

3.813 inches

**Body Length:**

7.563 inches

**Body Width:**

2.563 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

6.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

250.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.00 to 25.00 actuation point pounds per square inch and +0.00 to 25.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Stimulus Rating:**

3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

600.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0