NSN 5930-00-121-2269

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-121-2269

| 3 |
|--|
| Thread Class: |
| 2b all threaded hole |
| Inside Diameter: |
| 0.250 inches single connection |
| Overall Length: |
| 2.376 inches |
| Overall Height: |
| 2.641 inches |
| Overall Width: |
| 0.938 inches |
| Body Length: |
| 2.188 inches |
| Body Height: |
| 2.641 inches |
| Distance Between Mounting Facility Centers: |
| 0.688 inches |
| Pressure Switch Type: |
| Differential |
| Mounting Method: |
| Base and threaded hole |
| Features Provided: |
| Capillary tube end seal connection |
| Thready Qty Per Inch (tpi): |
| 32 all threaded hole |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.250 inches single pressure connection |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 8.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 140.00 actuation point pounds per square inch gage and 220.00 deactuation point pounds per square inch gage and 80.00 differential point |

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

pounds per square inch gage

NSN 5930-00-121-2269

Pressure Switch - Page 2 of 2

Fiig: A048b0



| Pressure Connector Type: |
|--|
| Swivel nut, compression, threaded internal single connection |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Rectangular |
| Thread Series Designator: |
| Unc all threaded hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |