NSN 5930-00-121-2273

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-121-2273

Thread Class:
2b all threaded hole
Inside Diameter:
0.250 inches single connection
Overall Length:
2.376 inches
Overall Height:
2.641 inches
Overall Width:
0.938 inches
Body Length:
2.188 inches
Body Height:
2.641 inches
Distance Between Mounting Facility Centers:
0.688 inches
Pressure Switch Type:
Differential
Mounting Method:
Base and threaded hole
Features Provided:
Capillary tube end seal connection
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
8.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
20.00 actuation point pounds per square inch gage and 13.00 deactuation point pounds per square inch gage and 7.00 differential point

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

pounds per square inch gage

NSN 5930-00-121-2273

Pressure Switch - Page 2 of 2

Fiig: A048b0



Pressure Connector Type:
Swivel nut, compression, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No