

View Online at <https://aerobasegroup.com/nsn/5930-00-122-1736>

Overall Length:

5.500 inches

Overall Height:

4.000 inches

Overall Width:

2.125 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.094 inches

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.375 inches

Longest Vertical Distance Between Mounting Centers:

4.969 inches

Pressure Switch Type:

Gage

Mounting Method:

Flush and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

40.00 actuation point pounds per square inch and 35.00 deactuation point pounds per square inch and 5.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

24.0 ac at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0