NSN 5930-00-122-2503

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-122-2503

Thread Class:

2a single mounting facility

Thread Length:

0.270 inches single mounting facility

Overall Length:

1.880 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.880 inches single actuator

Overall Diameter:

0.612 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-122-2503

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

0.2 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0