

View Online at <https://aerobasegroup.com/nsn/5930-00-122-3467>

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

First Flat Length:

0.250 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

8 single section front

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes 1st section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0