## NSN 5930-00-122-3491

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-122-3491
Thread Class:
2b single mounting facility
Overall Length:
3.136 inches
Overall Height:
1.625 inches
Overall Width:
1.450 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.000 inches single actuator
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Switch Contact Basic Design:
Pile-up
Mounting Method:
Threaded hole single mounting facility
Features Provided:
Cam actuated
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Contact Voltage Rating In Volts:
250.0 ac at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Cam Actuated Switch Contact Arrangement:
4 pole, double throw, one position momentary each switch each section in-line
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:

Tab w/screw

## NSN 5930-00-122-3491

Rotary Switch - Page 2 of 2



^	۸n	tar	٠.	SW	itc	hin	a	<b>\ct</b>	ion	
U	u	ιaι	jι	JW	ILC	ш	u /	<b>1</b> 01	IUII	

Breaks before makes each section in-line

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

15.0 amperes resistive load ac at sea level

Style Designator:

In-line, cam actuated

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0