NSN 5930-00-122-3492

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Corrosion resistant

Overall Length:

0.781 inches



View Online at https://aerobasegroup.com/nsn/5930-00-122-3492

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches
Overall Height:
0.586 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.285 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.340 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
7.0 grams
Switch Actuating Force:
40.0 grams
Actuator Movement:
Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 turret

NSN 5930-00-122-3492

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0