# NSN 5930-00-122-8625

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-122-8625

## **Thread Class:**

2b single mounting facility

### Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

### **Overall Length:**

0.500 inches

#### **Overall Height:**

1.692 inches

**Overall Width:** 

Between 1.356 inches and 1.376 inches

## **Distance Between Mounting Facility Centers:**

1.168 inches single mounting facility and 1.188 inches single mounting facility

## Individual Section Quantity:

1

## **Operating Tempurature Range:**

-65.0 to 100.0 degrees celsius

## **Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

#### Actuator Type:

Thumbwheel single actuator

## Thready Qty Per Inch (tpi):

56 single mounting facility

## **Thread Size:**

0.086 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

10 single actuator

## Terminal Type:

Printed circuit

## **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

## **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

## Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

# Color:

White single indicator marking

## **Precious Material And Location:**

Stator surfaces gold

Code Indicating Wheel Switch - Page 2 of 2

**Precious Material:** 

Gold

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0

