

View Online at <https://aerobasegroup.com/nsn/5930-00-122-8628>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

0.500 inches

**Overall Height:**

1.692 inches

**Overall Width:**

Between 1.356 inches and 1.376 inches

**Distance Between Mounting Facility Centers:**

1.168 inches single mounting facility and 1.188 inches single mounting facility

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0 to 100.0 degrees celsius

**Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Thready Qty Per Inch (tpi):**

56 single mounting facility

**Thread Size:**

0.086 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5 single section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions single section

**Special Features:**

Switch stopped to limit actuator rotation

**Color:**

White single indicator marking

**Precious Material And Location:**

Stator surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular indicating

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0