## NSN 5930-00-122-8628

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-122-8628

## **Thread Class:**

2b single mounting facility

## **Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:** 

0.500 inches

## **Overall Height:**

1.692 inches

#### **Overall Width:**

Between 1.356 inches and 1.376 inches

## **Distance Between Mounting Facility Centers:**

1.168 inches single mounting facility and 1.188 inches single mounting facility

## **Individual Section Quantity:**

1

## **Operating Tempurature Range:**

-65.0 to 100.0 degrees celsius

## **Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

## **Actuator Type:**

Thumbwheel single actuator

## Thready Qty Per Inch (tpi):

56 single mounting facility

## **Thread Size:**

0.086 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## **Switch Actuator Indexing Position Quantity:**

6 single actuator

## **Terminal Type:**

Printed circuit

## **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

## **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5 single section

## **Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions single section

## **Special Features:**

Switch stopped to limit actuator rotation

#### Color:

White single indicator marking

# NSN 5930-00-122-8628

Code Indicating Wheel Switch - Page 2 of 2



Precious Material And Location:
Stator surfaces gold
Precious Material:
Gold
Style Designator:
Rectangular indicating
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0