

View Online at <https://aerobasegroup.com/nsn/5930-00-123-9982>

**Body Style:**

Hole mounted

**Overall Length:**

0.510 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.281 inches

**Overall Height:**

0.535 inches

**Overall Width:**

0.200 inches

**Body Length:**

0.510 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.093 inches

**Actuator Free Position Height:**

0.355 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

1.5 ounces

**Switch Actuating Force:**

Between 3.0 ounces and 8.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes resistive ac and 3.000 amperes inductive ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0