NSN 5930-00-124-0054

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-124-0054

| Body Style: | | | | | |
|---|--|--|--|--|--|
| Hole mounted | | | | | |
| Hazardous Locations/environmental Protection: | | | | | |
| Dustproof | | | | | |
| Overall Length: | | | | | |
| 0.766 inches | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | |
| 0.610 inches | | | | | |
| Overall Height: | | | | | |
| 0.665 inches | | | | | |
| Overall Width: | | | | | |
| 0.137 inches | | | | | |
| Body Length: | | | | | |
| 0.468 inches | | | | | |
| Body Width: | | | | | |
| 0.137 inches | | | | | |
| Body Height: | | | | | |
| 0.343 inches | | | | | |
| Case Material: | | | | | |
| Metal | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | |
| 0.040 inches | | | | | |
| Actuator Style: | | | | | |
| Round | | | | | |
| Actuator Diameter: | | | | | |
| 0.062 inches | | | | | |
| Actuator Height: | | | | | |
| 0.179 inches | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 50.0 dc | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Method: | | | | | |
| Threaded hole | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 1 pole, single throw, normally open, momentary action single switch unit | | | | | |
| Switch Release Force: | | | | | |
| 4.0 inch-ounces | | | | | |
| Switch Actuating Force: | | | | | |
| 40.0 grams | | | | | |
| Contact Load Current Pating At Maximum Pated Voltage: | | | | | |

150.000 milliamperes resistive dc

NSN 5930-00-124-0054

Sensitive Switch - Page 2 of 2



| Р | recious | Material | And | Location: |
|---|---------|----------|-----|-----------|
|---|---------|----------|-----|-----------|

Contact and terminal surfaces gold

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0