

View Online at <https://aerobasegroup.com/nsn/5930-00-124-0056>

**Body Style:**

Hole mounted

**Overall Length:**

Between 0.735 inches and 0.765 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.245 inches and 0.255 inches

**Body Width:**

Between 0.345 inches and 0.355 inches

**Body Height:**

Between 0.490 inches and 0.530 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.084 inches and 0.094 inches

**Actuator Style:**

Round

**Actuator Free Position Height:**

0.446 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

22.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes lamp ac

**Test Data Document:**

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-8805 spec.