

View Online at <https://aerobasegroup.com/nsn/5930-00-124-0056>

Body Style:

Hole mounted

Overall Length:

Between 0.735 inches and 0.765 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.245 inches and 0.255 inches

Body Width:

Between 0.345 inches and 0.355 inches

Body Height:

Between 0.490 inches and 0.530 inches

Unthreaded Mounting Hole Diameter:

Between 0.084 inches and 0.094 inches

Actuator Style:

Round

Actuator Free Position Height:

0.446 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

22.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.