## NSN 5930-00-124-9779

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-124-9779

**Body Style:** 

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Between 0.872 inches and 0.878 inches

**Body Length:** 

Between 1.079 inches and 1.109 inches

**Body Width:** 

Between 0.401 inches and 0.411 inches

**Body Height:** 

Between 0.610 inches and 0.640 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.113 inches and 0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

**Switch Actuator Quantity:** 

1

**Actuator Length:** 

1.063 inches

**Actuator Style:** 

Leaf

**Actuator Width:** 

0.313 inches

**Actuator Free Position Height:** 

0.438 inches

**Actuator Adapter Style:** 

Leaf

**Maximum Voltage Rating In Volts:** 

277.0 ac and 250.0 dc

**Inclosure Type:** 

Fully enclosed

**Mounting Method:** 

Press fit

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

10.0 grams

**Switch Actuating Force:** 

75.0 grams

**Actuator Movement:** 

Between 0.110 pretravel inches and 0.200 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

0.200 amperes resistive dc and 11.000 amperes resistive ac

## NSN 5930-00-124-9779

Sensitive Switch - Page 2 of 2



One mounting hole; actuator seal not included

**Terminal Type And Quantity:** 

3 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0