NSN 5930-00-126-0527

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-126-0527

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Driptight
Overall Length:
3.700 inches
Overall Height:
2.094 inches
Overall Width:
1.570 inches
Actuator Length:
5.560 inches
Actuator Style:
Adjustable arm
Actuator Diameter:
0.125 inches
Actuator Height:
0.250 inches
Housing Length:
3.700 inches
Housing Width:
1.570 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.190 inches
Maximum Voltage Rating In Volts:
480.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 10.000 amperes resistive ac

NSN 5930-00-126-0527

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0