# NSN 5930-00-126-1653

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-126-1653

#### **Thread Class:**

2b single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

4.000 inches

### **Overall Height:**

2.000 inches

#### **Overall Width:**

2.000 inches

### Individual Section Quantity:

6

## Knob Manufacturer Code:

82121

### Knob Manufacturer Part Number:

А

## Longest Horizontal Distance Between Mounting Centers:

1.641 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

1.641 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

### **Throw Quantity:**

1 each section rear

### **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

### Thready Qty Per Inch (tpi):

24 single mounting facility

### **Thread Size:**

0.190 inches single mounting facility

### **Contact Voltage Rating In Volts:**

125.0 ac at sea level

### Mounting Facility Pattern:

Four position rectangular single mounting facility

# Switch Actuator Indexing Position Quantity:

2 single actuator

#### **Terminal Type:**

Tab w/screw

# NSN 5930-00-126-1653

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes each section rear

#### Switch Actuator Positioning Increment:

90.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

## Style Designator:

Tap, circuit selector

#### Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A052b0