

View Online at <https://aerobasegroup.com/nsn/5930-00-126-1667>

Thread Class:

2b

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.670 inches

Overall Height:

1.930 inches

Overall Width:

0.470 inches

Bushing Length:

0.170 inches

Body Length:

0.670 inches

Body Width:

0.470 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Height:

0.440 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.320 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms24655 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0