

View Online at <https://aerobasegroup.com/nsn/5930-00-126-1751>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.643 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.312 inches single actuator

Overall Diameter:

1.015 inches

Individual Section Quantity:

6

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

270.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+12.000 to 60.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0