

View Online at <https://aerobasegroup.com/nsn/5930-00-127-4224>

**Body Style:**

Hole mounted

**Overall Length:**

1.155 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.495 inches and 0.505 inches

**Overall Height:**

0.766 inches

**Overall Width:**

0.250 inches

**Body Length:**

Between 0.766 inches and 0.796 inches

**Body Width:**

Between 0.235 inches and 0.265 inches

**Body Height:**

Between 0.751 inches and 0.781 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.083 inches and 0.093 inches

**Actuator Length:**

Between 0.110 inches and 0.140 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.085 inches and 0.115 inches

**Actuator Width:**

Between 0.085 inches and 0.115 inches

**Actuator Free Position Height:**

Between 0.381 inches and 0.401 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

24.0 ounces

**Switch Actuating Force:**

21.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0