

View Online at <https://aerobasegroup.com/nsn/5930-00-127-7299>

Thread Class:

2a single mounting facility

Thread Length:

0.440 inches single mounting facility

Overall Length:

5.770 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.250 inches single actuator

Overall Diameter:

1.000 inches

Nonturn Device Radius:

0.375 inches at 6: 00 o'clock

Individual Section Quantity:

10

Nonturn Device Type:

Tab at 6: 00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

Helicopter, sea king h-3; aircraft, tomcat f-14; helicopter, carrier based asw, sh-60f; helicopter, ch-53a/d/e; helicopter, search and rescue, hh-60h; helicopter, lamps mark iii, sh-60b; helicopter, uscg search and rescue, hh-60j; helicopter, sea knight h-46

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0