

View Online at <https://aerobasegroup.com/nsn/5930-00-127-7299>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.440 inches single mounting facility

**Overall Length:**

5.770 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.250 inches single actuator

**Overall Diameter:**

1.000 inches

**Nonturn Device Radius:**

0.375 inches at 6: 00 o'clock

**Individual Section Quantity:**

10

**Nonturn Device Type:**

Tab at 6: 00 o'clock

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**End Application:**

Helicopter, sea king h-3; aircraft, tomcat f-14; helicopter, carrier based asw, sh-60f; helicopter, ch-53a/d/e; helicopter, search and rescue, hh-60h; helicopter, lamps mark iii, sh-60b; helicopter, uscg search and rescue, hh-60j; helicopter, sea knight h-46

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

7 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0