NSN 5930-00-128-1868

Hazardous Locations/environmental Protection:

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-128-1868

Watertight
Overall Length:
5.000 inches
Overall Height:
4.156 inches
Overall Width:
2.688 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
245.0 degrees fahrenheit
Mounting Method:
Bracket
Contact Action Stimulus:
Increase
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.6 amperes resistive load fourth voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+140.00 to 215.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Frequency In Hertz:
60.0 single voltage

NSN 5930-00-128-1868

Thermostatic Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0