

View Online at <https://aerobasegroup.com/nsn/5930-00-128-9272>

Thread Length:

0.375 inches single mounting facility

Overall Height:

Between 1.484 inches and 1.516 inches

Overall Width:

Between 1.422 inches and 1.454 inches

Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Length:

0.718 inches single actuator and 0.782 inches single actuator

Nonturn Device Radius:

0.438 inches at 9:00 o'clock

Nonturn Device Type:

Tab at 9:00 o'clock

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.5 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0