NSN 5930-00-131-9987

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-131-9987

Overall Length:
0.692 inches
Overall Height:
0.521 inches
Body Diameter:
0.605 inches
Body Height:
0.327 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
0.531 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
260.0 degrees celsius and -54.0 degrees celsius
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
more description of the second
Mounting Facility Pattern:
Mounting Facility Pattern:
Mounting Facility Pattern: Two position in-line
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 149.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Precious Material And Location:

NSN 5930-00-131-9987

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc w/flange
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0