

View Online at <https://aerobasegroup.com/nsn/5930-00-132-0891>

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

2.245 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.306 inches

Individual Section Quantity:

2

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+0.500 to 3.000 inch-pounds single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level and 75.0 milliamperes inductive load dc at sea level

Special Features:

2 semiconductor device diodes mil-s-19500/193, type 1n457, cr-7 connected to terminal 2 and 4 of first deck, cr-21 connected to terminal 2 and 7 of first deck

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0