# NSN 5930-00-132-2628

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-132-2628

# Thread Class:

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.781 inches

#### **Overall Height:**

1.047 inches

#### **Overall Width:**

1.000 inches

#### First Flat Length:

0.500 inches single actuator

### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

1.656 inches single actuator

### **Nonturn Device Radius:**

0.375 inches at 2: 00 o'clock

# Individual Section Quantity:

4

### Nonturn Device Type:

Tab at 2: 00 o'clock

## **Operating Tempurature Range:**

-65.0 to 100.0 degrees celsius

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

10 single actuator

## Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section front

# NSN 5930-00-132-2628

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0