# NSN 5930-00-132-2630

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-132-2630

# **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

4.406 inches

### **Overall Height:**

1.047 inches

#### **Overall Width:**

1.000 inches

#### First Flat Length:

0.500 inches single actuator

### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

1.656 inches single actuator

# Individual Section Quantity:

6

# **Operating Tempurature Range:**

-65.0 to 85.0 degrees celsius

### Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

### **Mounting Method:**

Threaded bushing single mounting facility

### Thread Size:

0.375 inches single mounting facility

### **Contact Voltage Rating In Volts:**

30.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

10 single actuator

#### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section front

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-132-2630

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

50.0 milliamperes resistive load ac at sea level

#### **Precious Material And Location:**

Contacts and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### **Demilitarization:**

No

#### Fiig:

A052b0