NSN 5930-00-132-2630

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-132-2630

Thread	Class:
--------	--------

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.406 inches

Overall Height:

1.047 inches

Overall Width:

1.000 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.656 inches single actuator

Individual Section Quantity:

6

Operating Tempurature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-132-2630

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

50.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0