

View Online at <https://aerobasegroup.com/nsn/5930-00-132-2662>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

13.188 inches

**Overall Height:**

1.875 inches

**Overall Width:**

1.719 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.513 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

14

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-65.0 to 85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

18 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

20.0 degrees single actuator

**Detent Rotational Torque Range:**

+2.000 to 8.000 inch-ounces single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

**Special Features:**

Dummy terminals located at position 5 for sect. 1 3 5 7 9 11 13 front position 8 rear dummy terminals located at position 3 and 4 for sect. 2 4 6 8 10 12 14 front and position 4 and 8 rear

**Precious Material And Location:**

Contacts and rotor blades silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0