NSN 5930-00-133-3015

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-133-3015

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

1.962 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

Between 1.000 inches and 1.306 inches

Individual Section Quantity:

1

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 single section

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-133-3015

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

75.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0